

Fire Extinguishers

JACTONE PREMIUM RANGE

ABC Powder

BS EN 3
Licence No. KM 57904

CE
0086

BAFE
BS EN3
PORTABLE EXTINGUISHER
MANUFACTURE

MEDIUM ABC 40 Dry Powder

TYPE Stored Pressure

PROPELLANT Nitrogen

OPERATING PRESSURE 15 Bar (at 20°C)

TEST PRESSURE 27 Bar (EPS2 25 Bar)

✓ Quality deep drawn cylinders
(4, 6 & 9kg models only)

✓ High quality heavy-duty brass valves

✓ Colour coded handles and bases



UK Manufactured | Colour Coded | BS EN3 Certified



Product Specifications

EXTINGUISHER	2kg ABC Powder	4kg ABC Powder	6kg ABC Powder	9kg ABC Powder
PRODUCT CODE	EPS2	EPS4	EPS6	EPS9
CAPACITY	2kg	4kg	6kg	9kg
FIRE RATING	13A 70B C	21A 113B C	27A 183B C	43A 233B C
OPERATING TEMPERATURE	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C
AVERAGE DISCHARGE TIME	9.5 seconds	12.9 seconds	16.1 seconds	16.7 seconds
HEIGHT	391mm	411mm	517mm	552mm
DIAMETER	108mm	160mm	160mm	189mm
FILLED WEIGHT	3.2kg	6.95kg	9.55kg	13.6kg
EMPTY WEIGHT	1.2kg	2.9kg	3.5kg	4.5kg
PACKING SPEC (HxWxD)	393 x 159 x 117mm	415 x 175 x 175mm	529 x 177 x 177mm	549 x 205 x 205mm
REFILL PART NUMBER	See page 37	See page 37	See page 37	See page 37